ES-WD-FD-490-F-4

Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

FD-490-F-4

Cast Iron Parking Structure Drain

Specification

Watts FD-490-F-4 epoxy coated cast iron cast in place parking deck drain with 17" x 17" square anti-ponding top with membrane clamping flange, heavy duty self-closing hinged grate, aluminum sediment bucket, and no hub outlet.

Call customer service if you need assistance with technical details.

	Pipe Sizing Suffix Description					
Suffix						
2	2"(51) Pipe Size					
3	3 3"(76) Pipe Size					
4	4 4"(102) Pipe Size					
5	5 5"(127) Pipe Size (NH Only)					
6	6 6" Pipe Size					
8	8 8"(203) Pipe Size (NH Only)					
10	10"(254) Pipe Size (NH Only)					

Outlet Type			
Suffix	Description		
NH	No Hub (MJ)		
Р	Push On		
Т	Threaded Outlet		
Х	Inside Caulk		

Options		Load	Free Area
Suffix	Description	Rating	Sq. In.
-13	All Galvanized	XHD	41

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

NOTICE

The load classifications are in accordance with the American National Standard ASME A112.21.1M ASME Ratings are as follows: XHD Safe Live Load 7500-10,000 lbs. (3375-4500 kg) The above categories are given as a guide only. Please consult factory.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com Canada: T: (888) 208-8927 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com



